

JPI FS-450 Quick Reference Guide

No Fuel Added

1. On initial power up, see “FILL ? n”
2. Tap STEP to exit

Reset Fuel Used

1. Tap STEP until “USD” indicator lights up
2. Hold AUTO for 3 seconds to reset fuel used to 0

Filled Tank

In flight, do steps 1-3 first (on power-up, skip to step 4)

1. Hold both STEP and AUTO until you see “ProG ModE”, followed by “FUEL ? n”
2. Tap AUTO and see “FUEL ? y”
3. Tap STEP
4. See “FUEL GAL” followed by “FILL ? n”
5. Tap AUTO and see “FILL 48*”
 - a. With tabs, tap AUTO again and see “FILL 34*”
6. Tap STEP to exit

Added or Removed Fuel

In flight, do steps 1-3 first (on power up, skip to step 4)

1. Hold both STEP and AUTO until you see “ProG ModE”, followed by “FUEL ? n”
2. Tap AUTO and see “FUEL ? y”
3. Tap STEP
4. See “FUEL GAL” followed by “FILL ? n”
5. Tap AUTO 2 or 3 times and see “FILL Add”
6. Tap STEP and see “0.0 GAL”
 - a. Hold AUTO to increase
 - b. Tap AUTO to decrease
7. Tap STEP to exit

Reset Alarm

- **Temporary reset (next 10 minutes):** Tap STEP
- **Reset for remainder of flight:** Hold STEP until “OFF” appears

JPI FS-450 Quick Reference Guide

Resuming Auto-Scan

1. Tap AUTO

Parameter Descriptions

USD	Total fuel used
REM	Fuel remaining (in gallons)
H.M.	Time to empty (in hours)
REQ	Fuel required to next GPS WPT or Destination
RES	Fuel reserve at next GPS WPT or Destination
REQ & RES	Nautical miles per gallon